



MARLDON LIQUID WAX CARE 1 LTR MXC700 / MXC705

CLEAR: 950058

WHITE TRANSPARENT: 950102

PRODUCT DESCRIPTION

Marldon Liquid Wax Care MXC 700 is a specifically designed maintenance and care product for the periodic treatment of wood floors and surfaces with a waxed or oiled finish. It is also suitable for the treatment of furniture including work tops and table tops and can be easily polished.

Marldon Liquid Wax Care is recommended for the initial treatment of freshly installed factory finished hardwax oiled floors. Ideal for cleaning and maintaining heavily used surfaces, this product removes stubborn marks with ease, including scuff marks from shoes and water spots, whilst enhancing the water resistant protective layer. Periodic care with Marldon Liquid Wax Care protects the surface, regenerates and replenishes the finish all in one simple application.

Along with the many benefits above, Marldon Liquid Wax Care also boasts a R9 slip resistant rating making it the ideal product for the maintenance of your oiled or waxed wooden floor.

COLOURS

Clear - ideal for natural and dark oiled timbers

White transparent - ideal for lighter and white oiled timbers



KEY BENEFITS

- ✓ Quick and economical.
- ✓ Removes heavy stains and stubborn heel marks.
- ✓ Coverage: 100m²/litre.
- ✓ Enhances the water resistancy of the floor.
- ✓ Suitable on all types of timber including hardwoods.
- ✓ Cleans and maintains.
- ✓ Dry in just 45 minutes!

CERTIFICATION AND COMPLIANCY

Slip resistant R9.

Flammable - after drying normally inflammable (EURO-Norm EN 13501- DIN 4102).

Flashpoint: over 28°C according to DIN 53213 (VbF-identification after EURO-Norm not required).



MARLDON LIQUID WAX CARE

1 LTR MXC700 / MXC705

CLEAR: 950058

WHITE TRANSPARENT: 950102

CONTAINS	Hydrocarbons C9-C11, isoalkanes, cycloalkanes, <2% aromatics. Repeated exposure may cause skin dryness or cracking. Working temperature: between 15°C to 25°C.
COVERAGE	Approximately 100m ² per litre.
DRYING TIME	Approximately 45 minutes, dependent on conditions.
APPLICATION METHOD	Apply one cap of Marldon Liquid Wax Care per 1m ² area of floor to be treated. Spread equally and thinly with no visible laps to untreated surfaces. Polish with a cloth and replace soiled cloths when necessary.
RECOMMENDED USE	For initial treatment of freshly installed factory finished hardwax oiled floors. Cleans and maintains heavily used surfaces. Removes stubborn marks with ease, including scuff marks from shoes and water spots whilst enhancing the water resistant protective layer.
TOTAL CURING TIME	Cures in approx 45 minutes dependent on the conditions and temperature - ideally leave for 1-2 hours before heavy foot traffic or replacement of furniture.
SLIP RESISTANCY	R9
OPEN TIME	Approx. 20 minutes working time once removed from original container. Only remove the required amount of product from the tin. The product must be sealed sufficiently before storage.
COLOUR	Clear = Caramel White Transparent = White
STORAGE	Store in a closed container at room temperature. Liquid Wax Care is not susceptible to frost. To restore good spreadability after exposure, store at room temperature for several hours and stir well.
SHELF LIFE	Unlimited in a closed container.
PACKAGING	Available in 1ltr tins. 6 x 1ltr tins per box.
CLEANING	Solvent based brush cleaner.
DISPOSAL	Wash out any product-soaked rags immediately or store in an airtight container. Flammable liquid and vapour.
DENSITY	0.75 - 0.81 g/cm ³
FLASHPOINT	27 °C
ODOUR	Faint/mild-odourless when dry.

This information is given to the best of our knowledge but without liability.



MARLDON LIQUID WAX CARE 1 LTR MXC700 / MXC705

CLEAR: 950058

WHITE TRANSPARENT: 950102

PREPARATION

Before using Liquid Wax Care, the surface must be cleared of all loose particles which could otherwise damage the floor. Underfloor heating must be switched off in good time before maintenance. Protect the floor from direct sunlight before, during and after application.

APPLICATION

For the application of Marldon Liquid Wax Care we recommend simply an oil cloth that should be replaced when necessary. Never use steel chips, a microfiber mop or abrasive cleaners.

Ensure that the area of the floor is clean and totally free from dust and any other contaminants before applying - the use of a vacuum cleaner is recommended.

Shake well before use then pour one capful (sufficient for cleaning of approx. 1 sqm) onto the dust cleaned surface and rub equally with a cloth. Be sure to apply pressure evenly across the floor.

We recommend applying Liquid Wax Care approximately once every 3 months,

especially in high traffic areas such as walkways, doorways and underneath dining tables.

For the removal of stubborn stains, pour a small quantity of Marldon Liquid Wax Care on the floor and rub off stains with a cloth. Concentrate on the area following instructions for general maintenance. Focus on the affected area for a period of time making sure to blend in to the surrounding area.

Following application, clean all brushes and tools with a solvent based brush cleaner or white spirit. Make sure that you clean them before the oil has completely dried.

MAINTENANCE

Wood surfaces treated with Liquid Wax Care do not require any further special care but regular cleaning is necessary.

We recommend the use of the following products: Marldon Cleancare (950059) - a concentrated cleaning solution specifically formulated for the day-to-day cleaning of oiled and hardwax oiled surfaces. Marldon Multicleaner (950115) - a ready to use multi-purpose cleaning solution ideal for use with a variety of day-to-day cleaning equipment including the Marldon spray mop.

For more information on these products please see the individual technical data sheets.

Safety data sheets available on request.

HEALTH & ENVIRONMENT

- Keep out of the reach of children.
- Do not fill into food, beverage or other containers used for foodstuffs.
- Flammable liquid and vapour. The dried coating is normally inflammable.
- Keep away from heat/sparks/open flames/hot surfaces and use non sparking tools.
- No smoking.
- Wash out any product-soaked rags immediately or store in an airtight container.
- May cause drowsiness or dizziness - avoid breathing vapours.
- Harmful to aquatic life with long lasting effects.
- If on skin (or hair), Take off all contaminated clothing immediately and rinse skin with water.
- If inhaled, remove yourself into fresh air and rest in a comfortable breathing position. If you feel unwell, call a doctor.
- In case of fire, use dry chemical or sand.
- Store in a well-ventilated place and keep container tightly closed.
- Use protective goggles and gloves.

Refer to the Health and Safety data sheet for further information.

FOR FURTHER INFORMATION

Contact the dedicated Marldon Technical Team on 01772 696600.

Additional Information: This data sheet is prepared by Marldon Technical Department. The information contained in this technical data sheet is based on present knowledge and current national legislation. The information provided is a guidance on usage, application, health and safety etc, it is not to be construed as a guarantee of technical performance or suitability for particular applications.