

REFRESHER

DIRECTIONS FOR USE

- The lacquered surface must be clean, dry, free from dust, grease, and soap residues. Oiled, waxed, or polished floors are not suited for treatment with Refresher.
- Mix Junckers SylvaNeutralizer with warm water and wash the floor. Then leave the floor to dry.
- Wet a flat thick-piled microfiber floor mop in warm water and wring out the mop hard.
- Mount the mop to the mop base and spray a thin S-shaped line of Refresher directly onto the floor.
- Use the mop to spread the Refresher and make sure to work in the longitudinal direction of the floorboards.
- Apply in an even layer and work in small sections of 3-4m².
- Remember to keep overlaps between the individual sections moist.
- Always apply Refresher to the entire floor area to ensure a uniform appearance and gloss level.
- Leave to dry for 1-2 hours before walking on the floor. If the floor is very worn, re-treatment can be conducted after 3 hours. Wait 24 hours to place furniture and rugs on the floor.
- Before treatment of the full floor, it is recommended to conduct a trial application in an inconspicuous area. After drying check the appearance of the floor and adhesion by scraping the surface with the edge of a coin.
- *If the lacquered surface is worn through to bare wood:*
Refresher cannot not be used if parts of the existing lacquer surface is worn through to bare wood. In this case the floor must be sanded and re-lacquered.

