

# MF-1 BITUMEN PAPER 25M<sup>2</sup> ROLL 150066

## PRODUCT DESCRIPTION

BS 1521 Grade Bitumen Building Paper

Manufactured with wet-strength kraft paper and meeting the technical requirements of BS 152, Class A1F, for water-proof building papers, the product utilises polymer reinforcing scrim.

Used where conditions require a material with additional strength and durability.

Ideal for use beneath a nail down timber floor when installing directly onto a timber substrate.

Typical uses: Moisture barrier, Underlays on uninsulated cladding, Separation Layers, Bond Breaks, Draught and Damp exclusion barriers.

Sizes available: 1000 mm x 25m



<b>MOISTURE VAPOUR RESISTANCE</b>	Min of 53 MNs/g
<b>TENSILE STRENGTH BS 4415 (DRY)</b>	Min of 12.4 kN/m (M/D), 7.20 kN/m (C/D)
<b>BURSTING STRENGTH BS 3137 (DRY)</b>	Min of 550 kN/m <sup>2</sup>
<b>LIQUID WATER RESISTANCE MIN.</b>	24 Hours
<b>UPPER TEMPERATURE STABILITY</b>	Over 70 Celsius
<b>CHEMICAL RESISTANCE</b>	Resistant to chemicals found in plaster and cement
<b>BIOLOGICAL</b>	Does not attract insects or vermin
<b>AVERAGE GRAMMAGE</b>	268gsm

This information is given to the best of our knowledge but without liability.

For more information  
Contact the dedicated Marldon  
Technical Team on 01772 696600.

Additional Information: This data sheet is prepared by Marldon Technical Department. The information contained in this technical data sheet is based on present knowledge and current national legislation. The information provided is a guidance on usage, application, health and safety etc, it is not to be construed as a guarantee of technical performance or suitability for particular applications.