

MARLDON M-323 RUBBER CRUMB UNDERLAY 150113

PRODUCT DESCRIPTION

The Marldon M-323 Rubber Crumb Underlay has been specifically developed for the use with wood and laminate flooring.

With a relatively light weight design and built-in metalised scrim, this underlay delivers excellent sound insulation and also ensures good resistance to moisture transmission.

A low tog rating of just 0.8 makes this underlay the ideal product for use with underfloor heating systems.

Manufactured from a high content of recycled tyres.



INSTALLATION

All aspects of the installation must be in accordance with the requirements of the relevant British standards and supplementary specifications.

Roll out underlay silver side up. DPM joining tape is recommended to seal the joints between adjoining rolls of underlay to seal the vapour barrier.

Roll Width	1m
M ² Per Roll	15m ²
Thickness	3.5mm
Weight Per m ²	ca. 1.26kgs
Impact Sound Reduction	23 dB
Tog Rating	0.8 TOG
Compression after dynamic loading	1.8mm
Moisture Barrier Properties	Typical value 0.5
Colour	Silver foil backing

KEY BENEFITS

- ✓ 3.5mm Thickness
- ✓ Excellent impact sound insulation
- ✓ Good resistance to moisture transmission
- ✓ High content of recycled tyres
- ✓ Ideal for underfloor heating
- ✓ Tog 0.8

FOR FURTHER INFORMATION

Contact the dedicated Marldon Technical Team on 01772 696600.

Additional Information: This data sheet is prepared by Marldon Technical Department. The information contained in this technical data sheet is based on present knowledge and current national legislation. The information provided is a guidance on usage, application, health and safety etc, it is not to be construed as a guarantee of technical performance or suitability for particular applications.